

www.strap-it.it



Full Strap

WWW.STRAP-IT.IT

POLYPROPYLENE STRAP - STANDARD LENGTH PER ROLL

SIZE	A 62 mm	B 392 mm	C 200 mm	D 150 mm	E 280 mm	K 406 mm
5 x 0,35			7500	7500		
5 x 0,40			7500	7500		
5 x 0,45			7000	7000		
6 x 0,50			6500			
9 x 0,50			4500		3700	
9 x 0,60			4000		3000	
9 x 0,65			3500		2800	
9 x 0,70			3250			
12 x 0,52	1500		3500		2800	3000
12 x 0,58	1250	3000	3000		2500	3000
12 x 0,65	1100	2750	2750		2200	2750
12 x 0,68	1000	2600	2600			2600
12 x 0,70	1000	2500	2500			2500
12 x 0,75		2500	2500			2300
12 x 0,80	750	2000	2000			2000
12 x 0,85		2000	2000			2000
15 x 0,60	750	2000	2000			2000
15 x 0,70		1800				1800
15 x 0,75		1500				1500
15 x 0,80	600	1500	1500			1500
15 x 0,85		1500	1500			1500
19 x 0,80		1300				1300

STAMPA PERSONALIZZATA FINO A 3 COLORI - PRINTED STRAP UNTILL 3 COLOURS ON REQUEST
For the sunlight exposure we suggest a special anti-UV product

DATI TECNICI

MATERIALE IMPIEGATO:

polipropilene isotattico

PESO SPECIFICO:

0,91g/cm³

RESISTENZA:

28 - 32 Kg/mm²

ALLUNGAMENTO:

15 - 25%

RECUPERO ELASTICO:

90 - 95%

TEMPERATURA D'ESERCIZIO:

da - 40 a +100°C

Tolleranza su tutti i dati enunciati: ±5%

COLORI:

bianco, nero e trasparente, a richiesta altri colori.



Full Strap
Advanced Strapping Systems

Full strap srl

Via delle Industrie 11 - 13856 Vigliano Biellese (BI)

Tel. +39 015 3353310 - Fax +39 015 3353313

info@fullstrap.com - www.fullstrap.com

P.Iva/C.F. 02575380023

TECHNICAL DATA

USED MATERIAL:

isotactic polypropylene

ABSOLUTE WEIGHT:

0,91g/cm³

RESISTANCE:

28 - 32 Kg/mm²

ELONGATION:

15 - 25%

ELASTIC FEEDBACK:

90 - 95%

WORKING TEMPERATURES:

from - 40 to +100°C

Tolerance on all the mentioned data: ±5%

COLOURS:

white, black and transparent, other colours upon request